

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06T 17/40, A45D 44/00	A1	(11) International Publication Number: WO 98/21695 (43) International Publication Date: 22 May 1998 (22.05.98)
(21) International Application Number: PCT/US97/20733 (22) International Filing Date: 12 November 1997 (12.11.97) (30) Priority Data: 08/747,351 12 November 1996 (12.11.96) US (71) Applicant: MIRROR SOFTWARE CORPORATION [US/US]; 12530 - 128th Lane N.E., Kirkland, WA 98034 (US). (72) Inventors: BLANCHARD, Perin; 22519 N.E. 165th Court, Woodinville, WA 98072 (US). VELLA, Shon; 23530 - 53rd Avenue S.E., Bothell, WA 98021 (US). LINFORD, Ray, A.; 14128 - 126th Place N.E., Kirkland, WA 98034 (US). (74) Agent: TULLETT, Rodney, C.; Christensen O'Connor Johnson & Kindness PLLC, Suite 2800, 1420 Fifth Avenue, Seattle, WA 98101 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>With amended claims and statement.</i>
(54) Title: IMAGING SYSTEM FOR SIMULATING HAIR STYLES		
(57) Abstract		
<p>An aesthetic imaging system (20) for superimposing a hair style (204) on the image of a client (152). The hair style is selected from an index of hair styles (202) and displayed to a system operator on the client's image. The displayed hair style is semitransparent so that the system operator may accurately position the hair style at a desired location on the client's image. A color matching region (154) defined by the system operator is used to copy the color of the client's hair to the displayed hair style (204). A mapping technique is disclosed which ensures that the color of the hair style (204) closely matches the color in the selected color matching region (154). An erosion tool is also provided to allow a system operator to erode the outer boundary of the hair style (204) in order to blend the hair style into the client's hair and also to simulate achievable hair replacement surgery results.</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div data-bbox="966 1155 1364 1438"> </div> <div data-bbox="1429 1302 1461 1344">A</div> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div data-bbox="982 1459 1299 1711"> </div> <div data-bbox="1396 1575 1429 1617">B</div> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div data-bbox="950 1732 1291 1984"> </div> <div data-bbox="1396 1806 1429 1848">C</div> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

IMAGING SYSTEM FOR SIMULATING HAIR STYLES

Field of the Invention

The present invention relates generally to computer imaging programs and, more specifically, to a method and system for superimposing hair styles on an image of a person.

Background of the Invention

Many people have recognized the benefits of a computer imaging system that would allow images of different types of hair styles to be superimposed over an image of a person. An imaging system that allowed a client to view different hair styles would be particularly helpful at hair salons in order to allow the client to examine many different styles and choose the one that is most desirable. An imaging system that simulated different hair styles would also be beneficial to the hair replacement industry. Simulating how a client or patient would likely look after hair grafts or hair transplants would simplify the decision of the client on whether to proceed with such a procedure. Many people have therefore tried to develop an imaging system that would quickly and easily allow a client to view different hair styles on their own image.

Several shortcomings have prevented the wide-spread use of hair style imaging systems. The first shortcoming of most imaging systems is that the systems do not accurately match the client's existing hair color with the simulated hair style that is applied over the client's image. Because the displayed hair style is a different color from the client's own hair, the applied hair style looks unnatural and artificial. Oftentimes many different colors of a hair style may be stored by the imaging system in an attempt to closely approximate the client's own hair color. Unfortunately, even

a slight difference in the color of the hair style and the color of the client's own hair is easily distinguishable when the hair style is applied to the image of the client.

An additional shortcoming of existing imaging systems is that it is often difficult to accurately locate the hair style on the client image. In order for a superimposed hair style to look natural, the hair style must be correctly positioned on the client's image. To allow accurate positioning of the hair, many existing systems superimpose the hair style using reference points that are entered by the system operator. For example, the system operator may locate reference points pinpointing the ears of the client so that the hair style may be positioned with respect to the ears. Unfortunately, the use of reference points does not adequately solve the placement problem. Using reference points slows the imaging process since it requires the additional step of requiring the operator to enter the reference points. Moreover, the use of reference points cannot be universally applied because of the different shapes of people's heads and the fact that most features on a person's head are not symmetric. As a result, most imaging systems are unable to achieve a realistic positioning of the hair style on the image of the client's head.

Still another shortcoming of existing imaging systems is that they are unable to simulate a receding hairline in a hair style. Simulating a receding hairline would be advantageous to show the effects of aging on an image of the client. Simulating a receding hairline would also be beneficial in the hair replacement industry, since the slight recession may more accurately represent the results achievable through transplant or graft procedures. Existing imaging systems are unable to accurately simulate a receding hairline.

Due to the above-mentioned shortcomings, imaging systems for the display of different hair styles have yet to be recognized or widely accepted by those in the hair style industry.

Summary of the Invention

The present invention provides an aesthetic imaging system for accurately displaying different hair styles on an image of an individual (hereinafter referred to as the "client"). The image of the client is captured by scanning a photograph into the imaging system or using a digital camera to capture the image. Once the image has been stored, the image is displayed on a computer monitor. The client or a system operator defines the color of the hair style to be displayed on the image by circling a region of the image containing the client's current hair. A number of hair styles are then displayed to the client in a hair style index. When a desired hair style is selected,

the color previously defined is mapped onto the hair style so that the hair style is displayed in the natural color of the client's hair. The client or system operator may then position the hair style on the image of the client. The resulting image looks natural because the hair style is displayed in the same color as the client's own hair.

5 In accordance with one aspect of the invention, a mapping technique is disclosed for mapping the color from the defined color matching region onto the hair style. The selected hair style is first converted to a greyscale image. The mapping technique then constructs histograms representing the red, blue, and green color channels in the selected region of the client's own hair, and a histogram of the
10 greyscale values in the hair style. The histograms are divided into a number of sections having an equal number of samples, and the sections used to map the colors represented in the red, green and blue histograms to the greyscale values in the greyscale histograms. The disclosed mapping technique generates a hair style that looks natural when added to the client's image since the hair style is the color of the
15 client's own hair.

In accordance with another aspect of the invention, when the hair style is initially displayed on the screen with the client's image, the hair style is displayed so that it is semitransparent. The client or system operator may position the hair style to a desired location because the underlying image of the client can be viewed through
20 the hair style. The translucency of the hair style therefore allows the accurate alignment and positioning of the hair style on the image of the client. The hair style may also be appropriately resized by lengthening, widening, or changing the rotation of the hair style. Once the desired position, size, and orientation of the hair style has been achieved by the system operator, the hair style is converted to an opaque image
25 so that the underlying image of the client cannot be viewed through the hair style.

In accordance with still another aspect of the invention, an erosion tool is provided in the aesthetic imaging system. The erosion tool causes the outer boundary of the hair style to slowly erode away. The amount of erosion is controlled by the client or system operator, and can be used to accurately simulate a receding hairline or
30 to more closely approximate the results achievable through hair replacement surgery.

It will be appreciated that the disclosed aesthetic imaging system offers several advantages over prior art systems. Because the color of the hair style is matched to the client's hair color and the hair style accurately positioned on the client's image, the client is presented with a very natural and realistic-looking image. Such an image
35 allows the client to make a more informed decision about selecting a hair style or

opting for hair replacement surgery. Moreover, the ability to erode the selected hair style when displayed on the client allows achievable surgical results to be more accurately simulated. By accurately simulating surgical results, the client can make a more informed decision about whether to pursue hair replacement surgery.

5

Brief Description of the Drawings

The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same becomes better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

10

FIGURE 1 is a block diagram of an aesthetic imaging system formed in accordance with the present invention;

FIGURE 2 is a flow chart illustrating an exemplary main routine by which digital images may be captured, stored, and viewed using a hair style simulation module in the aesthetic imaging system;

15

FIGURE 3 is an exemplary routine of the hair style simulation module that allows a hair style to be simulated on an image of a client;

FIGURES 4A-4C are pictorial representations illustrating the process of adding a hair style to a client's image;

20

FIGURE 5 is a pictorial representation illustrating a hair style selection dialog box from which a desired hair style is selected;

FIGURES 6A-6B are diagrammatic representations of the red, green, and blue (RGB) channels corresponding to the desired hair style and an alpha channel mask corresponding to the desired hair style and used to implement an erosion tool; and

25

FIGURES 7A-7B are a flow chart and a representative diagram of an exemplary routine for matching the color of a hair style with the color of the client's hair.

Detailed Description of the Preferred Embodiment

An aesthetic imaging system 20 formed in accordance with the present invention is illustrated in FIGURE 1. The aesthetic imaging system 20 includes an
30 imaging program 21 that runs on a processing unit 22 controlled by an operating system 24. A memory 26 is connected to the processing unit and generally comprises, for example, random access memory (RAM), read only memory (ROM), and magnetic storage media such as a hard drive, floppy disk, or magnetic tape. The processing unit and memory are typically housed within a personal computer 28 which
35 may be, for example, a Macintosh™, International Business Machines (IBM™) or

IBM-compatible personal computer. When used with IBM and IBM-compatible personal computers, the operating system 24 may be DOS based or may incorporate a windowing environment such as Microsoft Windows® or OS/2™.

5 The aesthetic imaging system 20 also includes an image capture board 30 that is coupled to the processing unit 22, a monitor 32, a video source 34, and a printer 36. The video source, monitor, and printer are coupled to the processing unit 22 through the image capture board 30. The video source may include one or more video cameras, a VCR, a scanner, or similar source for providing digital images to be edited by the aesthetic imaging system. The aesthetic imaging system further
10 includes a pointing device, preferably a stylus (pen) and tablet 38, that is connected to the processing unit 22. In addition, the aesthetic imaging system may include a modem 40 to provide on-line capabilities to users of the system, such as technical support and teleconferencing. The image capture board 30 has a plurality of buffers in high-speed memory, e.g., RAM, that are used by the imaging program 21 to allow
15 the quick manipulation of images. Suitable image capture boards for use in the aesthetic imaging system include the Targa +64 and Targa 2000 boards, distributed by Truevision, Inc. of Indianapolis, Indiana. Additional information about the operation of the hardware in the aesthetic imaging system 20 may be found in the commonly assigned, copending U.S. patent application Serial No. 08/406,201 entitled "Aesthetic Imaging System" (hereinafter the "Aesthetic Imaging System application"), the
20 drawings and specification of which are expressly incorporated herein by reference.

Prior to discussing the aesthetic imaging system in further detail, a compendium of terms used in the application may be helpful:

25	<i>Image</i>	A digital photograph or picture of a client.
30	<i>Stylus</i>	The "pen" that may be used to select menus, modify images, and carry out other commands in the program. The stylus controls the cursor, just as a mouse pointing device does on a personal computer.
35	<i>Tablet, or Pad</i>	The electronic notepad used in conjunction with a stylus. The pen must be held relatively close to the pad in order for the pen to communicate with the

5 tablet. Unlike a mouse, the tablet follows an X / Y grid that matches the monitor, i.e., if the pen is positioned at the top left corner of the tablet, the cursor is displayed at the top left corner on the monitor.

Floating Moving the pen to move the cursor, without actually touching the tablet.

10 ***Selecting*** Selecting (also referred to as "tipping" or "pressing") the tip of the pen briefly onto the tablet. This selects a command or affects the drawing tool, depending on the current procedure being implemented.

15 ***Cancel*** Using the side button on the pen to execute a command.

Moving Pressing the tip of the pen on the tablet, releasing it, then moving it across the tablet.

20

***Pressing or
Tipping &
Dragging***

25 Pressing the tip of the pen, then dragging it across the tablet while maintaining pressure. When using drawing and shaping tools, this turns the cursor into a drawing tool, enabling the user to draw freehand objects or "brush" the image in any manner.

30 FIGURE 2 illustrates an exemplary main routine executed by the processing unit 22 of the aesthetic imaging system 20 in order to implement the imaging program 21 in accordance with the present invention. At block 60, a system startup is performed wherein the computer looks for peripheral devices that are connected to the aesthetic imaging system, the memory is tested, and any other necessary startup procedures are implemented. At block 62, the imaging program displays a main
35 menu, which provides access to the various features of the imaging program.

Specifically, the main menu includes the following options that are pertinent to the present invention: *Storage*, *Camera*, *Hair Style*, and *Exit*. Each option is described in further detail below.

5 The first two main menu selections, i.e., *Storage* and *Camera*, allow a system operator to load an image of a client for editing. It will be appreciated that the aesthetic imaging system 20 may be implemented by a system operator specifically trained to use the system, or when convenient, by the client. However, for purposes of the following description, the aesthetic imaging system 20 will be described as being used by a system operator as a service to a client. The first option is to capture
10 an image of the client with the digital camera 34. Accordingly, at a decision block 64, a test is made to determine if the *Camera* option has been selected from the main menu. If the *Camera* option has been selected, at a block 66 an image of the client is captured using the digital camera and stored in the memory 26 of the aesthetic imaging system. The captured image is displayed to the system operator at a
15 block 68. After displaying the image of the client, the main routine returns to block 62.

The second option for obtaining an image to edit is to load a previously stored image. The previously stored image may have been scanned into the system from a photograph, or downloaded from a digital storage media. If the *Camera* option was
20 not selected, a test is made at a decision block 70 to determine if the *Storage* option has been selected. If the *Storage* option was selected, at a block 72 the image to be edited during the current session is selected by the system operator. The main routine then returns to block 62 where the main menu is again displayed.

Once an image has been loaded, the system operator may modify the image as
25 described in the copending Aesthetic Imaging System application above. In addition, the present invention allows the system operator to superimpose different hair styles on the image. At a decision block 76 a test is made to determine if the system operator has selected the *Hair Style* option from the main menu displayed at block 62. If the *Hair Style* option has been selected, a hair style module subroutine is called at
30 block 78. A suitable subroutine for implementing the Hair Style Module is depicted in FIGURE 3. If the *Hair Style* option is not invoked, the routine continues to a decision block 80.

At decision block 80 a test is made to determine whether the *Exit* option has been selected from the main menu. If the exit option is selected the program

terminates. Otherwise, the program returns to block 62 to allow the system operator to continue the selection of main menu options.

FIGURE 3 is a flow chart of an exemplary routine 100 for implementing the hair style module in the aesthetic imaging system 20. At a block 102 the selected
5 image of the client is displayed. FIGURE 4A is a representative screen 150 that is displayed by the imaging system 20 when the system operator selects an image. A frontal image 152 of the client is preferably displayed so that the entire head of the client is visible. It will be appreciated that other views of the client, including oblique or side views, may also be displayed if desired.

10 An advantage of the disclosed imaging system is that the client's hair color is used to color the hair style that is applied to the client's image. In order to define the client's hair color, at a block 104 the system operator defines a color matching region 154 of hair on the selected image 152 of the client. The color matching region is defined by using the cursor to circle a region anywhere within the client's present
15 hair. The size of the region that is selected dictates the range of colors that are mapped onto the selected hair style. A larger region which incorporates many different shades of the client's hair results in a more realistic mapping to the hair style as described in additional detail below. If the client does not have any hair from which to select a color matching region, it will be appreciated that a color spectrum or
20 other color chart may be displayed to the system operator to allow the system operator to select a desired hair color. Alternatively, the system operator may select a hair color from another client image stored in the aesthetic imaging system.

At a block 106, a hair style selection dialog box 200 as shown in FIGURE 5 is displayed. The dialog box contains a hair style index 202 that contains a number of
25 sample hair styles 204 that may be applied to a client's image. The hair styles in the hair style index may be captured from a variety of sources. Preferably, however, the hair styles within the hair style index are obtained by taking images of actual people and removing those portions of the captured images that do not correspond to the hair. The hair styles are therefore displayed in the hair style index 202 in the natural
30 hair color of the person from which the hair style was obtained. Using actual people's hair styles greatly improves the realism of the hair style when it is displayed on a client's image. The hair styles are depicted in miniature so that a number of styles may be viewed simultaneously.

The type of hair styles 204 that are displayed in the hair style index 202 is
35 dependent upon criteria that are selected by the system operator from a list of

criteria 206. That is, selecting different criteria causes the number and type of hair styles 204 that are displayed within the hair style index 202 to change accordingly. The criteria list contains a number of pull-down menus that allow the system operator to select qualities of the desired hair style. Preferably, the following qualities may be selected by the system operator: view, thickness, elapsed time, curl, grade, and gender. "View" is the view of the hair style that will be applied to the client, e.g., including but not limited to a front view, side view, or a top view. "Thickness" is the relative thickness, i.e., coarse versus fine, of the desired hair. Hair styles having coarse hair appear differently from hair styles having fine hair. "Elapsed time" suggests the amount of time following a hair transplant procedure. One of the types of hair styles that may be stored in the aesthetic imaging system are hair style from persons who have undergone a hair transplant procedure. Elapsed time allows the system operator to specify the length of time following the transplant procedure of the displayed hair styles. "Curl" allows the system operator to select hairstyles that vary from curly hair to straight hair. "Grade" is the overall quality of the hair. And, finally, "gender" determines whether the displayed hair styles are suitable for men, women, or are unisex. Each of the criteria may be specified by pulling down an associated menu and highlighting the desired choice. For example, in FIGURE 5 a pull-down menu 210 for the gender quality is currently highlighted to show the selected quality to be "male". Those of ordinary skill in the art will appreciate that the depicted hair style qualities are merely an illustrative sample of the type of qualities that may be provided for selection. Many other types of qualities can be provided in lieu of, or in addition to, those described above.

At a block 108, the system operator is allowed to select a desired hair style that is to be superimposed over the client's image using the dialog box 200. When the system operator finds a hair style in the hair style index 202 that the system operator would like to superimpose on the client's image 204, the system operator selects the hair style by positioning the cursor over the appropriate image in the hair style index 202 and tipping the pen on the tablet. Selecting a hair style highlights the box containing the hair style. For example, in FIGURE 5 the client has selected the third hair style from the left in the top row of the index. Following selection of the hair style, the system operator depresses an OK button 208 to return to the image of the client as shown in FIGURE 4B.

Prior to discussing what occurs after the system operator selects a hair style 204, it is necessary to describe how the selected hair style is stored in the memory 26

of the aesthetic imaging system 20. FIGURES 6A and 6B are representative diagrams of how each hair style 204 is stored in the aesthetic imaging system 20. FIGURE 6A depicts the color components of the hair style image 204. Each image in the aesthetic imaging system comprises a number of pixels, the color of each pixel defined by an 8-bit red component, an 8-bit green component, and an 8-bit blue component. It will be appreciated that the red, green, and blue (RGB) format for storing the pixels of an image is well-known in the art. The pixels inside an outer boundary 222 of the hair style are therefore each defined by a 24-bit value corresponding to the color of each pixel.

Also associated with each image is an alpha key channel that provides information about the opacity of each pixel. For each pixel in the image, the alpha key channel contains an 8-bit value that represents the transparency of the pixel when displayed or superimposed over another pixel. For a given alpha value, the following formula is used to determine the RGB value of the resulting pixel displayed to the system operator when an image having a first pixel is superimposed over an image having a second pixel:

$$(Y_1 * A) + (Y_2 * (1-A)) = Y_f \quad (1)$$

where:

Y_1 = the RGB value of the superimposed pixel

Y_2 = the RGB value of the underlying pixel;

Y_f = the RGB value of the displayed pixel; and

A = the alpha value corresponding to the superimposed pixel divided by 255.

An alpha value corresponding to zero therefore causes the superimposed pixel to be transparent, and an alpha value corresponding to xFF (255) causes the superimposed pixel to be opaque. In between these extremes, various amounts of the underlying pixel will be visible.

As represented diagrammatically in FIGURE 6B, the alpha channel is used to create an alpha mask 220 that corresponds to the superimposed hair style. The alpha values for those pixels outside of the boundary 222 of the hair style are set to 0 (transparent). Those pixels that fall within the boundary 222 of the hair style have an alpha value greater than zero. The transition of the alpha values from within the boundary to outside of the boundary may be abrupt, e.g., from alpha = 255 to alpha = 0. Preferably, however, the alpha values around the boundary of the hair style are stepped to smooth the boundary of the hair style. From the boundary of the hair

style, and proceeding toward the interior of the hair style, the alpha values incrementally increase from 0 to 255. While a first gradation 224 (of alpha = 100) and a second gradation 226 (of alpha = 200) are depicted in FIGURE 6B, it will be appreciated that a greater or lesser number of gradations may be included around the outer edge of the hair style. Moreover, while a linear gradation is depicted, it will be appreciated that the gradation may increase logarithmically or by another mathematical function. Those pixels in a central region 228 of the hair style have an alpha value of 255 (opaque). While separated for clarity in FIGURES 6A and 6B, it will be appreciated that the color pixel information and the alpha key channel information are preferably stored in memory 26 as a single image by the aesthetic imaging system 20.

After the desired hair style 204 is selected at block 108, the aesthetic imaging system 20 colors the hair style at a block 110 so that it matches the client's actual hair color as defined previously at block 104. FIGURE 7A depicts a preferred routine 250 for coloring the hair style so that the hair style matches the color of the client's hair. At a block 252 the RGB pixels in the selected hair style 204 are first converted to greyscale values. It will be appreciated that the conversion from color RGB pixel values to greyscale values are well-known to those in the art. At a block 254, a histogram of the greyscale pixel values in the selected hair style is constructed. The histogram represents a graph of the number of occurrences of each of the greyscale pixel values. It will be appreciated that depending upon the storage capabilities of the aesthetic imaging system 20, each selected hair style may already be stored with an associated histogram of its greyscale pixel values.

At a block 256, histograms are constructed for the color pixel information contained in the color matching region 154 previously defined by the system operator. Three histograms are constructed, one corresponding to the red channel, one corresponding to the blue channel, and one corresponding to the green channel of the pixels within the color matching region 154. The size of the histograms will obviously vary depending upon the size of the color matching region 154 that was selected by the system operator.

At a block 258, the histogram that was constructed at block 256 for each color channel is divided into N sections, each section having an equal number of samples (i.e., each section having an equal number of pixel value occurrences within the section). The histogram that was constructed at block 252 for the greyscale pixel values in the selected hair style 204 is also divided into N sections, each section

having an equal number of samples. It has been determined that $N = 40$ gives a realistic color mapping from the color matching region to the selected hair style for the majority of hair styles. It will be appreciated, however, that a greater or lesser value for N may be selected, with varying results depending upon the greyscale range within the selected hair style and the range of colors in the color matching region 154 defined by the system operator.

At a block 260, mapping tables are constructed between the histogram of the greyscale values in the selected hair style 204 and the histogram of each color channel from the color matching region 154. A mapping table is created for each section of each histogram pair, e.g. red-to-greyscale, green-to-greyscale, and blue-to-greyscale. Each mapping table is constructed by assigning the lowest greyscale pixel value in a given section to the color that corresponds to the lowest colored pixel value in the corresponding section of the color channel (red, green, or blue). The highest greyscale pixel value in a given section is assigned to the color corresponding to the highest colored pixel value in the corresponding section of the color channel (red, green, or blue). The remaining greyscale pixels are assigned to a value somewhere between the lowest and the highest RGB pixel values. To assign the remaining greyscale pixels, a linear interpolation is performed between the lowest colored pixel and the highest colored pixel in the corresponding section of each color channel. The remaining greyscale pixels are then mapped to the linearly interpolated values within each section.

The mapping of the histograms may be better understood with reference to FIGURE 7B. FIGURE 7B represents the mapping of a hypothetical greyscale histogram 270 having twelve greyscale levels (x_1 to x_{12}) with a red channel histogram 272 having nine red levels (y_1 to y_9). The y-axis of the histograms corresponds to the pixel values within the defined region or hair style, and the x-axis to the number of pixels within the defined region or hair style that have each pixel value. In the hypothetical mapping, $N = 2$. Each histogram is therefore initially divided into two sections having an equal number of samples. As shown in FIGURE 7B, each section in the greyscale histogram contains 59 samples (i.e., 59 occurrences of pixels having the values of x_1 to x_7 , and 59 occurrences of pixels having the values of x_8 to x_{12}), while each section in the red channel histogram contains 19 samples. A mapping table is then constructed between corresponding sections in the greyscale histogram 270 and the red channel histogram 272. Creating the mapping table for the first section, all pixels having a greyscale value of x_1 will be

mapped to the red pixel value of y_1 , and all pixels having a greyscale value of x_7 will be mapped to the red pixel value of y_5 . The pixels having a greyscale value of x_2 - x_6 are mapped to the red pixel values of y_2 - y_4 based on a linear interpolation between the red pixel values. A similar mapping table is created for the second section of the greyscale histogram and the red channel histogram. The step of building a mapping table for each section is also repeated for the other channels (green and blue) of the image.

When completed, the mapping tables describe how the color from the color-matching region 154 is mapped onto the selected hair style 204 in a realistic manner. Returning to FIGURE 7A, at a block 262, the color mapping is performed to convert the selected hair style 204 to the color of the client's hair. Because subtle shading and color are retained by the mapping method, the resulting hair style very closely simulates how the client's own hair would appear if styled in a similar manner.

Returning to FIGURE 3, after the selected hair style 204 has been colored to match the client's hair at block 110, at a block 112 the selected hair style is displayed on the image 152 of the client. With reference to FIGURE 4B, when the hair style 204 is initially displayed on the client's image 152, the hair style is displayed so that it is semitransparent. That is, the image of the client 152 may be seen through the image of the hair style 204. The image of the hair style is made semitransparent by changing the alpha values in the hair style alpha mask 220 so that the hair style is not opaque.

When displayed on a client's image 152, the hair style 204 is also surrounded by a sizing box 156. The sizing box allows the system operator to vary the size and orientation of the hair style. The size of the hair style may be adjusted by selecting either the top, bottom, or either side of the sizing box. Selecting the top or bottom of the sizing box and dragging the top or bottom upwards or downwards, respectively, stretches the vertical component of the hair style. Moving the top or the bottom towards each other compresses the vertical component of the hair style. Similarly, selecting either of the sides of the resizing box 156 and moving the sides inwardly compresses the horizontal component of the hair style 204. Moving the sides outwardly expands the horizontal component of the hair style. It will be appreciated that techniques for stretching or compressing an image in this manner are well-known to those skilled in the art.

Moreover, the hair style 204 may also be rotated to a desired angle. To rotate the hair style, the system operator selects a rotate menu option. When the rotate

option is selected, an axis 158 is displayed that extends from a center point 160 of the hair style. Using the cursor, the system operator may select the axis and rotate the axis around the fixed center point. As the axis rotates, the hair style is rotated an equal amount.

5 Returning to FIGURE 3, at a block 114 the system operator is allowed to position and size the hair style 204 on the client's image 152. To position the hair style, the system operator moves the cursor over the hair style, tips the pen on the tablet to select the hair style, and moves the hair style to the desired location by floating the pen over the tablet. Because the hair style is semitransparent, it is easy
10 for the system operator to accurately position the hair style at a desired location on the client's image. Moreover, the system operator may also resize and reorient the hair style during the positioning process so that it closely fits the size, shape, and orientation of the client's head. Another tip of the pen places the hair style on the image of the client. When placed on the image of the client, at a block 118 the hair
15 style is displayed in opaque form on the client's image. As shown in FIGURE 4C, the opaque hair style 204 covers the underlying portion of the client's image 152.

At a decision block 120, a test is made to determine if the system operator has correctly positioned the hair style on the client's image 152. If the system operator desires to reposition the image, the operator tips the pen when the cursor is located in
20 the resizing box 156. Tipping the pen returns the routine to block 112, where the hair style is made semitransparent. The system operator is then allowed to move, resize, and again place the semitransparent hair style on the image 152 of the client. If the system operator is satisfied with the position of the hair style at block 120, the operator tips the pen when the cursor is located outside of the resizing box 156.
25 Tipping the pen outside of the resizing box indicates that the hair style is correctly positioned. The routine then proceeds to a decision block 122. Because the system operator was able to accurately position the hair style 204 on the client's image 152, the displayed image closely simulates how the client would appear with the selected hair style.

30 At decision block 122, a test is made to determine if the system operator has selected an erosion tool. The erosion tool is provided by the aesthetic imaging system 20 to allow the system operator to more accurately blend the hair style with the client's own hair, to simulate the effect of a receding hairline, or to simulate achievable results from hair replacement surgery. The erosion tool may be selected
35 through a menu choice, function key, or other selection means known in the art.

The erosion tool uses the alpha mask 220 described above to erode the outer boundary of the selected hair style 204. With respect to FIGURE 6A, it will be appreciated that making the boundary 222 of the hair style 204 more transparent will allow more of the client's image 152 to show through the hair style around the edges.

5 Several different techniques may be used to erode the outer boundary. Preferably, however, the following incremental scheme is used to simulate the erosion of the hair style. An initial erosion step of the hair style is made by setting the alpha value of the first gradation 224 equal to 25. A second erosion step is made by setting the alpha value of the second gradation 226 equal to 50. Third and subsequent erosion steps
10 are made by adding additional gradations progressing inwardly from the boundary 222 towards the center of the hair style. The alpha values of the additional gradations progressively increase in steps of 25, i.e., the third gradation has an alpha value of 75, the fourth 100, etc. The boundary of the hairstyle is therefore made more transparent with each additional erosion step.

15 Preferably, the number of erosion steps performed on the hair style is tied to the movement of the cursor. At a block 124 and a block 126, an erosion step is performed on the hair style and the hair style displayed to the system operator. At a decision block 127, a test is made of the cursor position. As the system operator floats the cursor from the top of the screen to the bottom of the screen, the number of
20 erosion steps is changed. When the cursor is at the top of the screen, only a single erosion step is performed. When the cursor is at the bottom of the screen, ten erosions steps are performed. In between, the number of erosion steps varies between two and nine. The system operator may therefore view a variable amount of erosion by moving the cursor from the top to the bottom of the screen. When a desired
25 erosion amount is achieved, the erosion may be halted by tipping the pen on the tablet.

When the system operator has achieved a desired amount of erosion of the hair style 204, the routine continues to a block 128. At block 128 the image 152 of the client may be stored with the hair style superimposed over the image. It will be appreciated that after storing the image, the image may be subsequently manipulated
30 or printed out and provided to the client.

While the preferred embodiment of the invention has been illustrated and described, it will therefore be appreciated that various changes can be made therein without departing from the spirit and scope of the invention. The incremental erosion scheme described above is merely representative of one technique for making the
35 outer edges of the hair style more transparent. Other erosion schemes could also be

-16-

envisioned that would accomplish the same result. For example, the erosion steps may change the alpha values in the alpha mask 220 by a greater or a lesser amount than 25. The erosion steps may also be unequal, and increase logarithmically or based on another mathematical function. Moreover, the number of erosion steps that may be performed on the hair style may vary depending on the type of hair style. Some hair styles may be capable of being eroded with a greater number of steps, and some hair styles with a lesser number of steps. It will be appreciated that the type of erosion technique may therefore be varied for different hair styles. Consequently, within the scope of the appended claims it will be appreciated that the invention can be practiced otherwise than as specifically described herein.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. An aesthetic imaging system for simulating hair styles on an image of a client, the aesthetic imaging system comprising:

(a) storage means for storing an image of the client comprised of a plurality of pixels, and a plurality of hair style images comprised of a plurality of pixels;

(b) a monitor coupled to the storage means, the monitor capable of displaying a stored image;

(c) a controller coupled to the storage means and the monitor, the controller displaying the image of the client on the monitor and superimposing one of the plurality of hair style images over the image of the client, the displayed one of the plurality of hair style images being semitransparent so that the underlying image of the client may be viewed through the displayed hair style image; and

(d) a user input device coupled to the controller, the user input device allowing an operator of the aesthetic imaging system to move the selected hair style image on the monitor so that it may be accurately positioned on the image of the client.

-18-

AMENDED CLAIMS

[received by the International Bureau on 15 April 1998 (15.04.98);
original claim 1 cancelled; new claims 1-25 added (6 pages)]

1. An imaging system for simulating hair styles on an image of a client,
the imaging system comprising:

(a) a storage memory containing an earlier stored image of the
client comprised of a plurality of pixels, and a plurality of earlier stored hair style
5 images comprised of a plurality of pixels;

(b) a display coupled to the storage memory and capable of
displaying a stored image;

(c) a processor coupled to the storage means and the display, the
processor displaying the image of the client on the display and superimposing one of
10 the plurality of hair style images over the image of the client, the displayed hair style
image being substantially translucent so that the underlying image of the client may be
viewed through the displayed hair style image; and

(d) an input device coupled to the processor, the input device
allowing an operator of the imaging system to move a location of the displayed hair
15 style image on the display so that it may be accurately positioned on the image of the
client.

2. The imaging system of Claim 1, wherein the processor further displays
to the operator a subset of the plurality of earlier stored hair style images and allows
the operator to select one of the displayed subset to superimpose over the image of
20 the client using the input device.

3. The imaging system of Claim 2, further comprising means to allow an
operator to enter criteria about a desired hairstyle, the criteria determining the subset
of hair style images that are displayed to the operator.

4. The imaging system of Claim 1, wherein the input device further
25 allows the operator to resize the displayed hair style image.

5. The imaging system of Claim 1, wherein the input device further
allows the operator to rotate the displayed hair style image.

6. The imaging system of Claim 1, wherein after the displayed hair style image is accurately positioned on the image of the client, the processor manipulates the displayed hair style images so that it is opaque and displays the manipulated hair style image on the image of the client so that the underlying image of the client cannot
5 be viewed through the hair style image.

7. In an imaging system having a display, an input device, a processor to manipulate images, and a storage memory containing an earlier stored image of a client and a plurality of earlier stored hair style images, a method of positioning one of the plurality of hair style images on the image of the client in order to simulate a hair
10 style on the client, the method comprising the steps of:

(a) displaying the earlier stored image of the client on the display;

(b) manipulating one of the plurality of hair style images so that it is substantially translucent;

(c) displaying the substantially translucent one of the plurality of hair style images on the display so that the displayed hair style image is superimposed
15 over the image of the client; and

(d) allowing an operator to move the displayed hair style image on the display so that it may be accurately positioned on the underlying image of the client.

8. The method of Claim 7, further comprising the step of displaying a subset of the plurality of earlier stored hair style images and allowing the operator to select one of the displayed subset of hair style images for display on the image of the client.

9. The method of Claim 8, further comprising the step of allowing the
25 operator to enter criteria about a desired hairstyle, the criteria determining the subset of hair style images that are displayed to the operator.

10. The method of Claim 7, further comprising the step of allowing the operator to resize the displayed hair style image.

-20-

11. The method of Claim 7, further comprising the step of allowing the operator to rotate the displayed hair style image.

12. The method of Claim 7, further comprising the step of manipulating the displayed hair styles image so that it is opaque and the underlying image of the client cannot be viewed through the displayed hair styles image after the hair styles image is accurately positioned on the image of the client.

13. In an imaging system having a display with a cursor, a processor to manipulate images, and a storage memory containing an earlier stored client image comprised of a plurality of pixels and including a portion of the hair of the client and an earlier stored hair style image comprised of a plurality of pixels with a range of colors, a method of coloring the hair style image and displaying the hair style image on the earlier stored client image, the method comprising the steps of:

- (a) displaying the earlier stored client image to an operator on the display;
- (b) allowing the operator to define a region of the hair on the client image comprising a plurality of pixels with a range of colors;
- (c) mapping the range of colors from the defined region of the hair onto the stored hair style image so that the color of the hair style image approximates the color of the hair of the client; and
- (d) displaying the hair style image to the operator so that the hair style image is superimposed over the client image.

14. The method of Claim 13, further comprising the step of allowing the operator to manipulate the location of the hair style image so that the hair style image may be appropriately positioned on the client image.

15. The method of Claim 13, wherein the operator defines the region of the hair by manipulating the cursor to encircle an area on the client image.

16. The method of Claim 13, wherein the range of colors corresponding to the plurality of pixels in the defined region is specified by a red channel value, a blue channel value, and a green channel value associated with each pixel.

17. The method of Claim 16, wherein the step of mapping the range of
5 colors comprises the steps of:

- (a) constructing a first histogram of one of the red channel value, blue channel value, and green channel value corresponding to each of the plurality of pixels within the defined region;
- (b) constructing a second histogram of the range of colors
10 corresponding to each of the plurality of pixels in the hair style image;
- (c) dividing the first histogram into N sections and the second histogram into N sections;
- (d) constructing a plurality of mapping tables, each of the mapping tables mapping one of the N sections of the first histogram to a corresponding one of
15 the N sections of the second histogram; and
- (e) repeating steps (a)-(d) for the other two of the red channel value, blue channel value, and green channel value corresponding to each of the plurality of pixels within the defined region.

18. The method of Claim 17, wherein each of the N sections contains an
20 equal number of pixels.

19. The method of Claim 17, wherein the range of colors within the hair style image are greyscale values.

20. The method of Claim 17, wherein the range of colors corresponding to the plurality of pixels in the hair style image is specified by a red channel value, a blue
25 channel value, and a green channel value associated with each pixel.

-22-

21. The method of Claim 20, further comprising the step of converting the range of colors in the hair style image to greyscale values prior to constructing the second histogram.

22. In an imaging system having a display with a cursor, a processor to
5 manipulate images, and a storage memory containing an earlier stored client image comprised of a plurality of pixels and including a portion of the hair of the client and an earlier stored hair style image comprised of a plurality of pixels, a method of displaying the hair style image on the earlier stored client image, the method comprising the steps of:

10 (a) displaying the earlier stored client image to an operator on the display;

(b) displaying the earlier stored hair style image to the operator so that the hair style image is superimposed over the client image on the display;

15 (c) allowing the operator to manipulate the location of the hair style image so that the hair style image is appropriately positioned on the client image; and

(d) allowing the operator to erode an outer boundary of the hair style image so that the hair style image blends with the portion of the hair of the client in the client image.

20 23. The method of Claim 22, wherein step of eroding the outer boundary of the hair style image comprises the steps of:

(a) constructing an alpha mask comprised of a plurality of alpha values that range from an opaque value to a transparent value, the alpha mask having a shape that corresponds to an outer boundary of the shape of the hair style image and
25 each of the plurality of alpha values corresponding to one of the plurality of pixels in the hair style image;

(b) setting the plurality of alpha values in the alpha mask to the opaque value;

-23-

(c) associating the alpha mask with the hair style image so that a visibility of each of the plurality of pixels in the hair style image is determined by a corresponding alpha value in the alpha mask; and

(d) decrementing the alpha values around an outer boundary of the
5 alpha mask so that the alpha values approach the transparent value.

24. The method of Claim 23, wherein the amount of decrementing in step (d) is determined by the operator.


25. The method of Claim 24, wherein the amount of decrementing is determined by the motion of the cursor by the operator.

STATEMENT UNDER ARTICLE 19


Applicant requests that the claims be amended by substituting the attached replacement claim sheets. Claim 1 has been canceled and new Claims 1-25 have been added.

Applicant respectfully requests that the proposed amendment be entered prior to publication.


1/10



2/10

*Fig. 2*

3/10

*Fig. 3*

4/10





Fig. 4A

5/10

*Fig. 4B*

6/10




Fig. 4C

Figure 1 is a schematic diagram of a hair analysis system. The system includes a 'CRITERIA' section (206) with buttons for 'FRONT', 'VIEW', 'MEDIUM', 'THICKNESS', 'ELAPSED TIME', 'NONE', 'CURL', and 'GRADE'. A 'GENDER' section (210) has buttons for 'MALE', 'FEMALE', and 'UNISEX'. A '208' section has 'OK' and 'CANCEL' buttons. A '202' section is a 4x4 grid with icons in the first row and empty cells elsewhere. A '204' label points to the first three columns of the grid.

Fig. 5

8/10




Fig. 6A




Fig. 6B





Fig. 7A

10/10

*Fig. 7B*

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/20733

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06T17/40 A45D44/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 060 171 A (STEIR ET AL) 22 October 1991 see column 1, line 66 - column 2, line 34 see column 6, line 45 - line 52 see column 9, line 21 - column 11, line 7 ---	1
X	EP 0 725 364 A (MATSUSHITA ELECTRIC INDUSTRIAL CO. LTD.) 7 August 1996 see the whole document ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 096, no. 008, 30 August 1996 & JP 08 096111 A (TOSHIBA CORP), 12 April 1996, see abstract --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

2 March 1998

Date of mailing of the international search report

27. 03.98

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nicholls, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/20733

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 096, no. 010, 31 October 1996 & JP 08 147494 A (MATSUSHITA ELECTRIC IND CO LTD), 7 June 1996, see abstract ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 096, no. 010, 31 October 1996 & JP 08 153185 A (SONY CORP), 11 June 1996, see abstract ---	1
A	WO 96 29675 A (VIRTUAL EYES INCORPORATED) 26 September 1996 cited in the application see the whole document ---	1
A	US 4 731 743 A (BLANCATO) 15 March 1988 see the whole document -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/20733

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5060171 A	22-10-91	NONE	
EP 725364 A	07-08-96	JP 8329278 A	13-12-96
WO 9629675 A	26-09-96	US 5687259 A	11-11-97
		AU 5425196 A	08-10-96
		EP 0815533 A	07-01-98
US 4731743 A	15-03-88	US 4823285 A	18-04-89

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.